

CY7C1069AV33-1XW14

Status: NRND

CY7C1069AV33-1XW14	Y7C1069AV33-1XW14	
Automotive Qualified	N	
Density (Kb)	16384	
Frequency (MHz)	N/A	
Max. Operating Temp. (°C)	85	
Max. Operating VCCQ (V)	3.60	
Max. Operating Voltage (V)	3.60	
Min. Operating Temp. (°C)	-40	
Min. Operating VCCQ (V)	3.00	
Min. Operating Voltage (V)	3.00	
Organization (X x Y)	2M x 8	
Speed (ns)	0	
Temp. Classification	Industrial	

PRICING & INV	& INVENTORY AVAILABILITY				
1-9 unit	10-24 unit	25-99 unit	100-249 unit	250-999 unit	1000+ unit
Price*	Price*	Price*	Price*	Price*	Price*

Availability	Quantity	Ships In	Order Now
Out of Stock	0	Please click here to check lead times	Check Distributors**

 $[\]boldsymbol{\ast}$ Prices are shown in United States dollars and are for budgetary use only for volume of 1ku

^{} Check Distributors:** This part is sold through distributors only.

PACKAGING/ORDERING	ACKAGING/ORDERING	
No. of Pins	1	
Package Cross Section Drawing	Download	
Package Carrier	Bulk	
Package Carrier Drawing / Orientation	Package Orientation	
Minimum Order Quantity (MOQ)	1	
Order Increment	1	
Estimated Lead Time (days)		
HTS Code	8542.32.0040	

ECCN	(B.2.B.)
ECCN Suball	3A991

QUALITY AND ROHS		
Moisture Sensitivity Level (MSL)	5	
Peak Reflow Temp. (°C)		
RoHS Compliant	N Print RoHS Certificate of Compliance	
PB Free	N	
Lead/Ball Finish	N/A	
Marking	king Cypress Marking Format	
Device Qualification Reports		
FIT/MTBF, ESD (HBM/CDM) and Latch-up data available in the Device Qualification Report.		

QTP # 020804 : SYNCHRONOUS SRAM FAMILY TECHNOLOGY DERIVATIVE R7FT-1.8, FAB4 Last Update: Feb 20, 2014