

## **Specification Sheet**

Part Number: 181-15202



Solid Wall Wiring Duct, 1.5" X 2", Non-Adhesive, PVC, White, 120ft/Carton

Article Number	181-15202
Туре	SD1.5X2
Color	White (WH)
Features & Benefits	• Solid wall construction provides excellent coverage to keep wires clean. • Durable material protects wires from damage, with long-lasting performance. • A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. • Available standard colors complement or contrast in light and dark environments. • Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration. • Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement (Covers to be purchased separately.)
Quantity Per	carton

black, and is available in 6-foot lengths.	d colors of white, gray and
Short Description Solid Wall Wiring Duct, 1.5" X 2", Non-Adhesiv	e, PVC, White, 120ft/Carton
Global Part Name SD1.5X2-PVC-WH	
Technical Description Non-Adhesive	
Length L (Imperial) 6.0	
Length L (Metric) 1.83	
Width W (Imperial) 1.5	
Width W (Metric) 38.1	
Height H (Imperial) 2.07	
Height H (Metric) 52.60	
Mounting Hole Centers (Imperial) 4.0	
Material Polyvinylchloride (PVC)	

PVC

Self-Extinguishing

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and

**Product Description** 

**Material Shortcut** 

Flammability

Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)
Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Certification/Specification WEB	EN 50085-1:2005 + A1:2013 CSA UL EN 50085-2-3_1A
UL Recognized (US)	Yes
Package Quantity(Imperial)	120
Package Quantity (Metric)	36.58
Customs Number	3925900000

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

<sup>© 2018</sup> HellermannTyton. All rights reserved.