

Specification Sheet

Part Number: 181-11005



Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, White, 120ft/Carton

| Article Number | 181-11005 |
|---------------------|--|
| Туре | SD1X1 |
| Color | White (WH) |
| Features & Benefits | • Solid wall construction provides excellent coverage to keep wires clean. • Durable material protects wires from damage, with long-lasting performance. • A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. • Available standard colors complement or contrast in light and dark environments. • Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration. • Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement (Covers to be purchased separately.) |
| Quantity Per | carton |

| Product Description | protects wire. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths. |
|----------------------------------|--|
| Short Description | Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, White, 120ft/Carton |
| Global Part Name | SD1X1-PVC-WH |
| Technical Description | Non-Adhesive |
| | |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 1.0 |
| Width W (Metric) | 25.4 |
| Height H (Imperial) | 1.06 |
| Height H (Metric) | 26.90 |
| Mounting Hole Centers (Imperial) | 4.0 |
| | |
| Material | Polyvinylchloride (PVC) |
| | |

PVC

Self-Extinguishing

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and

Product Description

Material Shortcut

Flammability

| Halogen free | No |
|---------------------------------|--|
| Operating Temperature (Metric) | +122°F (+50°C) |
| Reach Complaint(Article 33) | No |
| ROHS Complaint | Yes |
| Certification/Specification WEB | EN 50085-2-3_1A UL CSA EN 50085-1:2005 + A1:2013 |
| UL Recognized (US) | Yes |
| | |
| Package Quantity(Imperial) | 120 |
| Package Quantity (Metric) | 36.58 |
| Customs Number | 3925900000 |

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

^{© 2018} HellermannTyton. All rights reserved.