



Electrical

Operating voltage : 250VAC max
 Current rating: 3Amps max
 Insulation resistance: 1000 Mohms min 500VDC
 Dielectric withstanding voltage: 1000VAC for 1MINUTE
 Operating temperature: -55c to +105c

RoHS compliant
 Unit: mm

6	UL1007 26AWG INSULATOR WIRE, LENGTH 60mm	25	M541
5	PCB: SAK-7 ELECTRO-PLATED HOOD	1	M730
4	SCREW 4*12.5mm, #4-40, WITH PAD ASSEMBLY TYPE	1SET	M16
3	HEX-NUT 5*6.6mm	2	M95
2	DB25 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108
1	DB25 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108
No.	DESCRIPTION	Q'TY	Supplier

Scale	Free
TOLERANCE	
X.	±1
X.X	±0.20
DIM	TOL
Angle	TOL

Drawn	11.08.2014	Joanna
Id.	①	
Modification		
Date	11.08.2014	Joanna

Drawn	11.08.2014	Joanna
Approved	11.08.2014	Joanna

Customer-No.	ASSMANN WSW-No. AB972
Drawing-No.	ASS 7208 CA
Replace	rev00
Sheet	

1	2	3	4	5	6	7
1	2	3	4	5	6	7