

E32-T14


| | |
|----------------------|--|
| Part Number: | E32-T14 |
| Fabrikant / Brand: | Omron Automation & Safety |
| Produkt beschreibung | SENS LONG DIST THRU BEAM SIDEVIEW |
| Datebanken: | PDF 1.E32-T14.pdf PDF 2.E32-T14.pdf |
| RoHS Status |  Bleif gratis / RoHS kompatibel |
| Ship From | Hong Kong |
| Shipment Way | DHL/Fedex/TNT/UPS/EMS |



Bild kann Representatioun sinn. Kuckt Spezifikatioune fir Produktdetailer.













Spezifikatioune vun E32-T14

| | |
|--|--|
| PART NUMBER | E32-T14 |
| HIERSTELLER | Omron Automation & Safety |
| BESCHREIWUNG | SENS LONG DIST THRU BEAM SIDEVIEW |
| BLEIF FREE STATUS / ROHS STATUS | Bleif gratis / RoHS kompatibel |
| DATENLABEL | PDF 1.E32-T14.pdf PDF 2.E32-T14.pdf |
| VOLTAGE - SUPPLY | - |
| SERIE | E32 |
| SENSING METHOD | Through-Beam |
| SENSING DISTANCE | 133.858" (3.4m) |
| RESPONSE TIME | - |
| AUSGABKONFIGURATIOUN | - |
| ANER NAMES | E32-T14-ND E32T14 Z5585 |
| OPERATIOUN TEMPERATUR | -40°C ~ 70°C |
| FEUCHTIGKEIT SENSIBILITÉITNIVEAU (MSL) | 1 (Unlimited) |
| FABRIK STANDARD LEAD TIME | 2 Weeks |
| LIICHTBRUNN | - |
| BLEIF FREE STATUS / ROHS STATUS | Lead free / RoHS Compliant |
| INGRESS PROTECTION | IP67 |
| CONNECTION METHOD | Cable |
| ADJUSTMENT TYPE | - |

Verbonnen Tags

| | | |
|-----------------------------------|-------------------------------------|---|
| Omron Automation & Safety E32-T14 | E32-T14 Distributeur | E32-T14 Ubidder |
| E32-T14 Präis | E32-T14 Fotoen | E32-T14 Bild |
| E32-T14 PDF Dateblatt | E32-T14 Luet Dateblatt | E32-T14 Dateblatt |
| E32-T14 Stock | Kaaft E32-T14 | Kaaft Omron Automation & Safety E32-T14 |
| Omron Automation & Safety E32-T14 | Omron Automation & Safety Ubidder | Omron Automation & Safety Distributeur |
| Omron Automation & Safety E32-T14 | Omron Automation and Safety E32-T14 | |

Verbonnen Produkter

| | |
|---|---|
|  <p>E32-T14L Produzentereuren: Omron Automation & Safety Beschreiwung: CABLE FIBER OPTIC FOR AMP 2PC PT Op Lager: 1 pcs RFQ</p> |  <p>E32-T12L 5M Produzentereuren: Omron Automation & Safety Beschreiwung: SENSOR FIBER OPTIC THRU BEAM 5M Op Lager: 5 pcs RFQ</p> |
|  <p>E32-T12F 5M Produzentereuren: Omron Automation & Safety Beschreiwung: SENS FLUOROESN 80CM THRU BEAM 5M Op Lager: Out stock RFQ</p> |  <p>E32-T12F-6 Produzentereuren: Omron Automation & Safety Beschreiwung: SENS FLUOROESIN 80CM THRU BEAM Op Lager: Out stock RFQ</p> |
|  <p>E32-T14 3M Produzentereuren: Omron Automation & Safety Beschreiwung: SENS LONG DIST THRU BEAM SIDE 3M Op Lager: Out stock RFQ</p> |  <p>E32-T14F Produzentereuren: Omron Automation & Safety Beschreiwung: SENS FIBER FLUOROESIN SIDEVIEW Op Lager: Out stock RFQ</p> |
|  <p>E32-T12R Produzentereuren: Omron Automation & Safety Beschreiwung: SENS HIGH FLEX T-BEAM 3MM DIA Op Lager: Out stock RFQ</p> |  <p>E32-T14LR Produzentereuren: Omron Automation & Safety Beschreiwung: SENS HI FLEX SIDEVIEW 3MM HEAD Op Lager: Out stock RFQ</p> |
|  <p>E32-T14L 5M Produzentereuren: Omron Automation & Safety Beschreiwung: SIDE VIEW 12CM LONG DIST 5M Op Lager: Out stock RFQ</p> |  <p>E32-T12L Produzentereuren: Omron Automation & Safety Beschreiwung: SENS LONG DIST THRU BEAM 2.2M Op Lager: Out stock RFQ</p> |
|  <p>E32-T14 5M Produzentereuren: Omron Automation & Safety Beschreiwung: SENS LONG DIST THRU BEAM SIDE 5M Op Lager: Out stock RFQ</p> |  <p>E32-T12F Produzentereuren: Omron Automation & Safety Beschreiwung: SENS FLUOROESIN 80CM THRU BEAM Op Lager: Out stock RFQ</p> |